



Motor Oil & Lubricants

REXOIL PREMIUM RACING 5W50 SN

REXOIL PREMIUM RACING 5W50 is full synthetic engine oil for ultimate performance in turbo and non-turbo petrol engines of racing, rally cars and passenger cars. **REXOIL PREMIUM RACING 5W50** is made of a proprietary blend of ultra-high performance synthetic base stocks fortified with a precisely balanced component system. This race-proven technology is suited for extreme driving conditions and motorsport applications.

Properties

- Have high viscosity index with enhanced film strength at high operating temperatures.
- Offers extra reserve needed to resist extreme operating conditions during rallying and racing.
- Prevents deposits and sludge build-up to enable long and clean engine life.
- Performs and protects at low temperatures
- Excellent protection against wear, corrosion and foam.

Approvals and Specifications

- API SN/SM/CF
- ACEA A3/B4-12 (2012)
- MB-Approval 226.5/229.3/229.5
- Opel GM-LL-B-025
- PSA Peugeot Citroën B71 2296
- Renault RN0710 / RN0700
- VW 502 00/505 00
- Porsche A40
- FORD WSS-M2C913-C
- FORD WSS-M2C913-D
- Opel GM-LL-A-025
- BMW Longlife - 01



Motor Oil & Lubricants

Technical Specifications

Test	Method	Typical Properties
Kinematic Viscosity (100°C), [cSt]	ASTM D445	17,0 – 21,5
Viscosity Index	ASTM D2270	Min. 160
HTHS Viscosity @ 150 °C, mPa.s	ASTM D4683	Min. 3,8
Cold Cranking Viscosity@ -30 °C, cP	ASTM D5293	Max. 6500
Flash Point, °C	ASTM D92	Min. 220
Pour Point, °C	ASTM D97	Max. -38
Total Base Number, mg KOH/g	ASTM D 2896	Min. 8,5