

CHROME 20W/50 SL/CF

Date of Issue Revision Date : 02.01.13 : 22.12.14

Revision : 01

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name and code	CHROME 20W/50 SL/CF
Product use	Multigrade Engine Oil
Producer/supplier	Reksoil Petrokimya San. Ve Tic. A.Ş
Address	Aydınlı Mh. Birlik Organize San. Böl. Doğu Cad. No: 19-21
	34953 Tuzla/İSTANBUL/ TÜRKİYE
	Tel: 0216 593 35 70 Fax: 0216 593 35 78

2. COMPOSITION / INFORMATION ABOUT INGREDIENTS

A mixture of base oil and performance additives.

CAS NO. / EC NO.	Chemical Composition	% Rate	Symbol(s)	Risk Phrase(s)
Mixture	Base Oil	65-95	-	-
68649-42-3 /	Zinc	<=1,6	N, Xi	R51/53
272-028-3	alkyldithiophosphate	~-1,0	14, 241	R36/38 R41
Proprietary	Methacrylate copolymer	<=0,1	Xi	R36



CHROME 20W/50 SL/CF

Date of Issue : 02.01.13 Revision Date : 22.12.14	Revision : 01
3. HAZARDS IDENTIFICATION	
Physical / Chemical Hazards	Not classified as dangerous.
Human health hazards	Not classified as dangerous.
Environmental Hazards	Not likely to be harmful to aquatic organisms.
4. FIRST-AID MEASURES Eye contact	Hold the eyelids apart with clean hands and flush with running water for at least 15 minutes.
Skin contact	Rinse thoroughly with running water and soap. Take off contaminated clothes and should be washed contacted area on skin with water. You should see the doctor if irritate keeps continue on the skin.
Ingestion	DO NOT induce vomiting! Wash the mouth out with water. In case of nausea or any other symptoms seek medical assistance and show the label/container.
Inhalation	Remove the person to fresh air. If the person has breathing difficulties, seek medical assistance.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishers And Fire Fighting Method	Should be used foam, dry chemical and water spry at small-scale fires. Should call fire department at large fire.
Unsuitable Extinguishers And Fire Fighting Method	Do not intervene fire with water.
Special Situations After Combustion	Toxic gases consist After Combustion. May burn at high temperatures.
Special protective equipment for Fire- fighting	Should be used protective clothing and oxygen mask for extinguishing Indoor locations fires by trained personnel.



CHROME 20W/50 SL/CF					
Date of Issue : 02.01.13 Revision Date : 22.12.14	Revision : 01				
6. ACCIDENTAL RELEASE MEAS	SURES				
Personal precautions	Use personal protective equipment from item 8. Stand upwind from the release site.				
Environmental precautions	Avoid spilling into water, sewerage and drainage systems by digging a protective ditch and/or setting up partitions of dry sand, soil or similar absorbent material. Use floating dams for water spills.				
Methods for cleaning-up and recovery	Absorb the spilt product with absorbent or inert material. Store the waste material and contaminated surface layer of soil that was removed in closed containers in well-ventilated premises. Hand over for disposal to legal entities for hazardous waste disposal, authorized by the Ministry in charge of environmental protection.				
Additional warnings	In case of larger spills, notify the communication unit at 112.				
7. HANDLING AND STORAGE					
Handling					
Safety precautions	Use product in well ventilated premises. Keep away from sources of heat and ignition.				
Safe handling advice	Avoid contact with skin and eyes.				
Storage: Technical measures and storag	Storage: Technical measures and storage conditions				
Suitable	It is recommended that base oil be stored in covered or closed area. Recommended storage temperature is 5-40 °C.				
To be avoided	Do not expose to direct sunlight or higher temperatures, avoid contact with water or strong oxidants.				

Packaging materials



CHROME 20W/50	SL/C	F
----------------------	------	---

Date of Issue: 02.01.13Revision Date: 22.12.14			Revision	: 01
8. EXPOSUE	RE CONTROLS / PER	SONAL PROTECTION		
Technical mea exposure	sures for reducing	Ensure good ventilation of premises.		
Control paran	neters	See item 7.		
Personal prote	ective equipment			
Respiratory p	rotection	During regular work respiratory protective equipme cases (e.g. spills) use full face protective mask and pressurized air breathing apparatus.	-	-
Hand protection	on	Gloves made of PVC or neoprene, resistant to oils,	greases, alkali and	l acids.
Eye protection	ı	Protective goggles with side protection or protectiv	e visor.	
Skin and body	protection	Protective clothes and footwear.		
Special hygien precautions	ic and safety	Smoking, eating and drinking is prohibited during hands before each work break.	handling this prod	duct. Wash
Additional wa	rnings	Immediately remove contaminated clothes and foot	wear.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Physica	l properties				
State:	Liquid	Color:	Amber	Odor:	Petroleum odor



CHROME 20W/50 SL/CF

Date of Issue Revision Date

: 02.01.13 : 22.12.14

Revision : 01

Chemical properties

Characteristics	Unit	Values	Method
Density @ 15 °C	g/cm ³	0,87-0,90	ASTM D 4052
Flash Point	°C	Min. 230	ASTM D 92
Kinematic Viscosity@100 °C	mm ² /s	16,3-21,9	ASTM D 445
Kinematic viscosity@100 C	11111/5	10,3-21,9	AS I M D 445

10. STABILITY AND REACTIVITY

Stability	Stabile at normal conditions.
Conditions to avoid	High temperature and direct sunlight.
Materials to avoid	Avoid contact with water and strong oxidants.
Hazardous decomposition products	Forming of dangerous products not expected at normal storage conditions.

11. TOXICOLOGICAL INFORMATION

Eye contact	If accidental eye contact can cause temporary blindness.
Skin contact	Prolonged or repeated contact can cause skin irritation. If skin contact with hot product that creates skin burns.
Ingestion	There is no any information.
Respiratory	Eye, nose and throat will be irritated if fog or mist breathes. Hot product vapor irritates the upper respiratory tract.



CHROME 20W/50 SL/CF			
Date of Issue : 02.01.13 Revision Date : 22.12.14		Revision	: 01
12. ECOLOGICAL			
Ecotoxicity	Does not harm the aquatic life forms. Spills mak prevent oxygen transfer.	ke film layer on	water and
Mobility	Spilled product will cause pollution of groundwater.		
Persistence and degradability	Have the ability to accumulate in the soil.		

13. DISPOSAL CONSIDERATIONS

According to current legislation should be eliminated by licensed personnel.

14. TRANSPORT INFORMATION

Transportation is not dangerous. Not classified as hazardous for transport.

15. REGULATORY INFORMATION

- S2 Keep out of the reach of children
- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S29 Do not empty into drains.
- **S39** Wear eye/face protection.
- S46 If swallowed, seek medical advice immediately and show this container or label



CHROME 20W/50 SL/CF			
Date of Issue : 02.01.13 Revision Date : 22.12.14		Revision	: 01
16. OTHER INFORMATION			
Relevant R Phrases			
R41	Risk of serious damage to eye.		
R38	Irritating to skin		
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic en-	vironment.	

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of this company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to the accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitableness and completeness of such information for his own particular use.